



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Disc door. IR remote sensor.

Touch buttons OPEN/CLOSE, DISC SELECT, RANDOM, ₩ BACK, NEXT ➤ Digital display.

■ STOP, II PAUSE, ➤ PLAY, STANDBY/ON (with indicator), POWER: ON OF OFF.



BACK PANEL: Power cord receptacle.

POWER CONTROL: IN and OUT. DATA control IN.

IR: SENSOR INPUT. COAXIAL DIGITAL AUDIO OUTPUT. OPTICAL DIGITAL AUDIO OUTPUT. RS232

remote CONTROL connector. UNBALANCED L & R AUDIO OUTPUT. BALANCED L & R AUDIO OUTPUT.

SPECIFICATIONS: Response: 5-20kHz (+0.5 -0.5dB). Dynamic Range: 100dB.
Signal to Noise Ratio: 108dBA. Separation: 105dB. Distortion: 0.002%.
Sampling Rate: 44.1kHz. Error Correction: cross interleaved Reed Solomon code (CIRC). Analog Output: 2.2V balanced or unbalanced. Digital Output: 0.5V p-p/75 ohm (coaxial); -15dBm--21dBm (optical). Has HR045 hand remote.

Power Requirements: 120 Volts, at 25 watts.











MCD 205 - Sold from 2002 - 2006. S/N: TT1001~TT???? (?,???? UNITS)

Size: 5-3/8"H, 17-1/2"W and 15"D behind panel. **Weight:** 21 lb. **\$3,200.00**