

FRONT PANEL: Glass with illuminated teal/gold nomenclature and anodized black aluminum panel. Disc drawer. IR remote SENSOR. REMOTE indicator. DAMAGED DISC/MUTE indicator. Digital display. SELECT, 1, 2, 3, 4, 5, 6, 7, 8, 9, 0, CLEAR, STORE, VOLUME, VOLUME ▼, PLAY, LOAD (with indicator), REV, FF ▶, REPEAT, PAUSE, STOP, TIME, BACK TRACK, NEXT TRACK. Output LEVEL control. HeadPHONES jack. PANLOC buttons.



BACK PANEL: DIGITAL OUTPUT. Left and Right FIXED OUTPUT. Left and Right VARIABLE OUTPUT. DIN REMOTE CONTROL connector. Power cord. Panloc mounting.

SPECIFICATIONS: Response: 20-20kHz (+0.3 -0.3dB). Dynamic Range: 96Db.
 Signal to Noise Ratio: 96dB. Separation: 94dB. Distortion: 0.003%.
 Sampling Rate: 176.4kHz. D/A Conversion: two 16 bit (quadruple oversampling).
 Error Correction: Cross-Interleaved Reed-Solomon Code (CIRC). Output Level: 2.7V. Readout: AlGaAs laser 800nm. Headphone Impedance: 8-1000 ohms.
 Has HR 7005 hand remote.

Power Requirements: 120 Volts, at ?? watts.

CABINET: L 52 Also fits L 11, L 12, and L 62

PANLOC BRACKETS: Right – **0??-???** / Left – **0??-???**

© 2007-2025 VintageMac – Larry Hodson

MCD 7005 SINGLE DISC CD PLAYER

MtIntosh The Compendium









 MCD 7005 - Sold from June 1987 - October 1988.
 S/N: EN1001~EN4000 (2,999 UNITS)

 Size: 5-7/16"H, 16-1/8"W and 13"D behind panel.
 Weight: 19-1/2 lb. \$1,599.00

© 2007-2025 VintageMac – Larry Hodson