

FRONT PANEL: Polished stainless steel/black chassis. LED/fiber-optic illuminated green nomenclature. IR sensor. Standby indicator.

Touch buttons: ■STOP, (with indicator), DISC LAYER. Digital display. Touch buttons: ▶ PLAY/ II PAUSE (with indicator), OPEN/CLOSE.

BACK - ► NEXT / PUSH - SETUP control. Disc tray. INPUT / PUSH - POWER control.



BACK PANEL: DIGITAL INPUTS: COAX 1, COAX 2 / OPTICAL 1, OPTICAL 2, USB AUDIO. SERVICE port. DATA PORT: IN / OUT. EXTERNAL CONTROL port: RS232 / IR IN. POWER CONTROL: IN / OUT. AUDIO OUTPUTS: BALanced R, BALanced L. UNBALanced L / R.

→ Power cord receptacle.

SPECIFICATIONS: Disc Media: CD, SACD, DVD (data). Fixed Output Level: 2.0Vrms Unbalanced; 4.0Vrms Balanced. Output Impedance: 100 ohms Unbalanced and Balanced. Signal to Noise Ratio: Better than 98dB (A-weighted). Harmonic **Distortion:** 0.02% @ 1000Hz. **Frequency Response:** ±0.5dB from 20Hz-20,000Hz. Power Control and Trigger Output: 12VDC, 25mA. Has hand remote HR450. Playable Disc Media Files:

Format	Up To Frequency/ Bit	Bit Rate
MP3 (.mp3)	48KHz	up to 320kbps
WMA (.wma)	48KHz	up to 320kbps
AAC (.aac/ mp4)	48KHz	up to 320kbps
WAV (.wav)	192KHz/24 Bit*	uncompressed
FLAC (.flac)	192KHz/24 Bit*	uncompressed
ALAC (.m4a)	96KHz/24 Bit*	uncompressed
AIFF (.aif/aiff)	192KHz/24 Bit*	uncompressed
DSD (.dff/dsf)	DSD128 (5.6MHz)	uncompressed

^{*}up to 48KHz with CD-R/+RW

Power Requirements: 120 Volts, at 35 watts.









MCD 85 - Sold from February 2021 - Current. S/N: ???1001~??????? (?,???? UNITS)

Size: 7-3/4"H, 12-5/32"W and 16-1/4"D. **Weight:** 20.5 lb. \$4,500.00