

MCT 450

SINGLE DISC SACD/CD PLAYER

McIntosh

The Compendium



FRONT PANEL: Glass with LED/fiber-optic illuminated green nomenclature. Disc tray. IR remote sensor. ⚡ Touch buttons: TIME, DISC LAYER, BACK ◀, NEXT ▶. Digital display. Touch buttons: ■ STOP, ▶ PLAY/II PAUSE, OPEN/CLOSE, STANDBY/ON (with indicator).



BACK PANEL: DIGITAL AUDIO OUTPUTS: XLR, DIN. POWER CONTROL: IN and OUT. DATA control IN. IR: sensor input. ⚡ DIGITAL AUDIO OUTPUTS: OPTICAL and COAXIAL. Power cord receptacle.

SPECIFICATIONS: **Digital Audio Output Format Coaxial, Optical and XLR:** SPDIF (PCM1), IEC958 Digital DIN: SPDIF (PCM1), IEC958 and DSD (SACD). **Digital Audio Outputs Coaxial:** 0.5V p-p/75 ohms **Optical:** - 15dbm to -21dbm (TOS Link) XLR: 0.5V p-p/150 ohms Digital DIN: 3V @110 ohms. **Digital Audio Output Sample Rates Coaxial:** Up to 24-Bit/96kHz **Optical:** Up to 24-Bit/192kHz **XLR:** Up to 24-Bit/192kHz, Up to 32-Bit/96kHz. **Transport:** Twin Beam laser. **Wavelength:** 650 nm (SACD)/790 nm (CD). **Laser Power:** CLASS IIa/CLASS I. Has **HR 450** hand remote.

Power Requirements: 120 Volts, at 35 watts.

- 1 PCM (Pulse Code Modulation) Digital Signal type used for CD Discs 2
- 2 DSD (Direct Stream Digital) Digital Signal type used for SACD Discs

MCT 450

SINGLE DISC SACD/CD PLAYER

McIntosh
The Compendium



MCT 450 - Sold from March 2015 - 2020. S/N: AEB1001~AEB???? (?,?,?,?, UNITS)

Size: 6"H, 17-1/2"W and 19"D. **Weight:** 29 lb. **\$4,000.00**