MVP 861 single disc dvd/cd player







BACK PANEL: 5.1 CHannel UNBALANCED AUDIO OUTPUT: CENTER and SUBWOOFER. SURROUND
Left and Right. FRONT Left and Right. UNBALANCED 2 CHannel OUTPUT: Left and Right.
BALANCED AUDIO OUTPUTS: Left and Right. COAXIAL DIGITAL AUDIO OUTPUT. OPTICAL DIGITAL
AUDIO OUTPUT. RS232 remote CONTROL connector. IR: sensor INput. DATA control
INput. POWER CONTROL: OUT and IN.
Composite VIDEO OUTPUT. S-VIDEO OUTPUT.
COMPONENT VIDEO OUTPUT: PR, PB and Y. Power cord receptacle.

SPECIFICATIONS: DVD: Response: 4-22kHz (48K sampling); 4-44kHz (96K sampling); DVD Audio: 4-88kHz (192 kHz sampling). CD Audio: 4-20kHz. Dynamic Range: >100dB, DVD and CD. CD S/N Ratio: 115dBA. Channel Separation: >110dB. Distortion: 0.002%. D/A Converters: three each 192hz/24 bit PCM/DSD Stereo DACs. Laser Beam Wavelength: 630/nm/810nm. Analog Output: 2.Vrms. Digital Output: 0.5V p-p/75 ohm (coaxial); -15dBmm-21dBm (optical). Video Output Levels: (75 ohms): Composite: 1 Vp-p; S-video: 1 Vp-p; Component: Y: 1 Vp-p; Pb: 0.648 Vp-p; Pr: 0.7 Vp-p. Video Out Adjustments: 4:3 Pan and Scan, 4:3 Letterbox, 16:9. MPEG digital noise reduction. Progressive scan (480P). TV *Type:* Direct View, CRT Projector, LCD Projector, Rear Projection. NTSC/PAL Region Code: 1. Compatible Disc Types: DVD-Video, DVD-RAM (4.7GB), DVD-Audio, 96/24 DTS, CD-Audio (CD-DA), CD-R, CD-RW, DVD-R, DVD-RW, MP3-CD, J-PEG Photo CDs, Video CD. Built-in SACD, DVD Audio, Dolby Digital and DTS decoder. Has **HR052** hand remote.

Power Requirements: 120 Volts, at 35 watts.

MVP 861 single disc dvd/cd player

MtIntosh The Compendium







MVP 861 - Sold from December 2004 - 2007. S/N: VT1001~VT???? (?,???? UNITS) Size: 5-3/8"H, 17-1/2"W and 13-1/8"D behind panel. Weight: 21-1/2 lb. \$4,100.00

© 2007-2025 VintageMac – Larry Hodson