

MHA200

TUBE HEADPHONE AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Polished stainless steel/black chassis. **LOAD** control: 32 Ω , 100 Ω , 250 Ω , 600 Ω . Standby/On indicator. **STANDBY/ON** power button. **VOLUME** control. ⚡
HEADPHONE OUTPUTS: 3 pin XLR Left, 3 pin XLR Right. 4 pin XLR STEREO. 1/4" STEREO jack.



BACK PANEL: INPUTS: UNBALANCED Left and Right, BALANCED Left and Right. POWER CONTROL: IN and OUT. Power cord receptacle.

MHA200

TUBE HEADPHONE AMPLIFIER

McIntosh

The Compendium

TECHNICAL SPECIFICATIONS: **Headphone Power Output:** 500mW into 32, 100, 250 or 600 Ohm Load. **Headphone Output Load Impedance:** 32-100 Ohms, 100-250 Ohms, 250-600 Ohms, 600-1000 Ohms. **Rated Power Band:** 20Hz to 20,000Hz. **Total Harmonic Distortion:** 0.5% maximum from 20Hz to 20kHz. **Dynamic Headroom:** 1dB 8 ohm load; 1.3dB 4 ohm load. **Frequency Response:** +0,-0.5dB, 20Hz to 20,000Hz. **Input Sensitivity (for rated output):** 1.0Vrms Unbalanced; 2.0Vrms Balanced. **A-Weighted Signal to Noise Ratio:** 94dB Unbalanced. **Voltage Gain:** 12dB 32 Ohm, 17dB 100 Ohm, 21dB 250 Ohm, 25dB 600 Ohm. **Trigger Output:** 12VDC, 50mA maximum. **Power Requirements:** 120V at 50 watts.

TUBES: (2) **12AT7** and (2) **12BH7A** dual triode vacuum tubes.



MHA200 - Sold from Feb. 2021 - Current. S/N: AJJ1011~AJJ????

Size: 5-3/4"H, 6-1/8"W and 9-1/8"D. **Weight:** 10.5 lb. **\$2,500.00**