| ドラレ 4 SURROUND DECODER / DOLBY DIGITAL AC-3, DTS | III≁IIIIU⊊II The Compendium |
|--|---|
| NOO DE REGEN DE SANTON | VCCCE |
| FRONT PANEL: Glass with illuminated teal/gold nomenclature. CD 1, SAT, LV, DVD. CHANNEL STATUS lights: L, C, R, LFE, L lights: DTS, DOLBY DIGITAL and PRO LOGIC. DELAY/VOLUME DELAY/SYS CAL control. WIR SENSOR. Touch button sw SURROUND, SYSTEM CALIBRATION, LATE NIGHT, RE-EQ+TM, POWE CENTER DELAY, SURROUND DELAY, VOLUME, STANDBY/ON / RESET. | S, S, RS. INPUT SIGNAL MODE digital display. VOLUME / itches with indicator lights: R: OFF or ON (with indicator), |
| | |

BACK PANEL: Power cord receptacle. OUTPUTS: Left SURROUND, CENTER, Left FRONT, Right SURROUND, SUBWOOFER, Right FRONT. Left & Right ANALOG INPUT. FP SENSOR switch: OFF or ON. DATA IN and OUT. POWER CONTROL IN and OUT. SYSTEM CALIBRATE switch: AUTO or MAN. SPEAKER SETTINGS switches: FRONT: SMALL or LARGE, CENTER: NONE, SMALL or LARGE, SURROUND: SMALL OR LARGE, SUBWOOFER: OFF or ON. DIGITAL OPTICAL INPUTS: DVD, LV, SAT, CD 1. DIGITAL COAXIAL INPUTS: SAT, CD 1, DVD, LV. LV RF AC-3 INPUT.

1000

0 0 0

SPECIFICATIONS: Frequency Response Stereo: Left and right small speakers: 80Hz-20,000Hz; subwoofer 20Hz to 80Hz; Left and right large speakers: 20Hz-20,000; subwoofer off. Frequency Response Pro Logic: Left, center, right small speakers: 80Hz-20,000Hz; surround 80Hz-7kHz; subwoofer 20Hz to 80Hz; Left, center, right large speakers: 20Hz-20,000Hz; surround 20Hz-7kHz; subwoofer off. Frequency response Dolby Digital and DTS: Left, center, right small speakers: 80Hz-20,000Hz; surround 80Hz-20kHz; subwoofer 20Hz to 80Hz; Left, center, right large speakers: 20Hz-20,000Hz; surround 20Hz-20kHz; subwoofer 20Hz to 80Hz; Left, center, right large speakers: 20Hz-20,000Hz; surround 20Hz-20kHz; subwoofer 20Hz to 80Hz. Rated Output: 2.0V for full bit (8.0V max). Output Impedance: 420 ohms at all outputs. Total Harmonic Distortion: 0.005% at all outputs. Sensitivity Analog Input: 0.5V for 2.0V output (2.0V full bit, 6.0V with AILC). Signal to Noise Ratio All Outputs: >100dB A weighted. Voltage Gain: 12Db.

 MSD 4 - Sold from: 1998 - 2000.
 S/N: PN1001~PN????

 Size: 3-9/16", 17-1/2"W and 17-1/2"D.
 \$3,250.00

1070 10 ·

© 2007-2025 VintageMac – Larry Hodson

Mrintoch