

MSE 1

SURROUND EXPANDER / DOLBY DIGITAL AC-3, DTS

McIntosh

The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Channel status: LS, BS, RS, SUB. Indicator for EXPAND mode. Digital readout for DELAY/TRIM. ⚡ Touch buttons: **MODE:** AUTO, MANUAL. **SYS CAL**, **DELAY**, **POWER:** OFF or ON (with indicator), ▼ **LEVEL**, **LEVEL** ▲, **TRIM** (with indicator), **STANDBY/ON**.



BACK PANEL: Power cord receptacle. **OUTPUTS:** Left / Right BACK 2, BACK 1 / SUBWOOFER, Left / Right SURR. Left / Right ANALOG INPUT. **DATA:** IN and OUT. **POWER CONTROL:** IN and OUT. **SYSTEM CALIBRATE** switch: AUTO or MAN. **SPEAKER SETTINGS:** BACK 2 and 1: NONE, SMALL or LARGE. **SURROUND:** SMALL, LARGE. **SUBWOOFER:** OFF or ON.

SPECIFICATIONS: **Frequency Response:** Surround small speakers: 80Hz-20,000Hz; subwoofer 20Hz to 80Hz; surround large speakers: 20Hz-20,000. **Rated Output:** 2.0V for full bit (6.0V max). **Output Impedance:** less than 100 ohms. **Total Harmonic Distortion:** 0.005% at all outputs. **Sensitivity:** 200 mV. **Signal to Noise Ratio All Outputs:** >98dB A weighted. **Voltage Gain:** unity from input to output, ±6dB with trim level.



MSE 1 - Sold from 2000 - 2001. S/N: SG1001~SG????

Size: 3-9/16"H, 17-1/2"W and 5-11/16"D. **Weight:** 19-1/2 lb. **\$2,500.00**