

# MA 6450

## STEREO INTEGRATED AMPLIFIER

# McIntosh

## The Compendium



EARLY



LATE

**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. TREBLE. Left POWER OUTPUT meter (linear WATTS or DECIBELS). POWER GUARD light. INPUT SELECTOR: CD 1, CD 2, TUNER, VIDEO and AUX. Right POWER OUTPUT meter (linear WATTS or DECIBELS). POWER GUARD light. VOLUME. Mute light. ⚡ BASS. IR sensor. Pushbutton switches with indicator lights: TAPE MON 1, TAPE MON 2, TAPE COPY: 1▶2 and 2▶1, MONO, SPEAKERS: 1 and 2, and POWER. Concentric BALANCE / LOUDNESS: FLAT to MAX. (Later units had a central POWER: OFF or ON switch. Right pushbutton switch became STANDBY/ON.)



**BACK PANEL:** DATA ports: TUNER, CD 2, CD 1, AUX, SUM, TAPE 2, TAPE 1, VIDEO. POWER AMP IN. POWER AMP INPUT switch: EXTERNAL or INTERNAL. OUTPUTS: MAIN, TAPE 2, TAPE 1. PROCESSOR: FROM. PROCESSOR switch: IN or OUT. PROCESSOR: TO. INPUTS: TAPE 2, TAPE 1, VIDEO, TUNER, CD 2, CD 1, AUX. ⚡ FUSE. Power cord. AC outlets: 1 UNSWITCHED, 1 SWITCHED. LEFT & RIGHT output barrier strips for SPEAKERS 1 and 2. Coax EXTERNAL SENSOR connector. POWER CONTROL jack.

# MA 6450

## STEREO INTEGRATED AMPLIFIER

# McIntosh

## The Compendium

**SPECIFICATIONS:** 100w/ch at 4 ohms. **Response:** 20-20kHz (+0 -0.5dB).

**Distortion:** 0.005%. **Dynamic Headroom:** 2.4dB. **Noise and Hum:** -100dB high level, -90dB low level re 10mV. **Damping Factor:** 40. **Input Sensitivity and Impedance:** high level 0.25V (10V max) at 22k, phono 2.5mV (90mV max) at 47k and 65pF, power amp 2.5V. Bass and treble boost or cut 12dB. **Power Guard. Sentry Monitor. Direct coupled.** Same as **MA 6400** but without headphone output and phono preamp. **Power Requirements:** 120V at 5 Amps. Has hand remote **HR 033** and **HR093** replacement.



EARLY



LATE

**MA 6450** - Sold from 1998 - 1999. S/N: Early - MC1001~MC???? Late - PC1001~PC????

**Size:** 5-3/8"H, 17-1/2"W and 18-1/8"D. **Weight:** 41 lbs. **\$2,200.00**