



FRONT PANEL: LED/fiber-optic illuminated green nomenclature. HEADPHONE jack. IR sensor. Touch buttons (with indicators): INPUT (with White/Red/Green/Blue indicator to indicate source), WI-FI/NET, ▼ VOLUME, ▲ VOLUME, STANDBY/ON.



BACK PANEL: WLAN ANTenna 1 connector. WLAN ANTenna 2 connector. ⚡ DC IN 5V power receptacle. TRIGGER IN/OUT. USB connector. AUDIO INPUTS: DIGITAL COAXIAL / OPTICAL, UNBALANCED Left / Right. AUDIO OUTPUTS: DIGITAL COAXIAL / OPTICAL, UNBALANCED Left / Right, BALANCED Right / Left.

AUDIO SPECIFICATIONS: *Frequency Response:* +/-0.5dB from 20-20,000Hz. *Total Harmonic Distortion:* 0.005%. *Sensitivity:* 200mV, Unbalanced. *Maximum Input Signal:* 2.Vrms Unbalanced. *Variable Output Level:* 0-6.0Vrms Unbalanced, 0-12.0Vrms Balanced. *Signal To Noise Ratio (A-Weighted):* 100dB. *Dynamic Range:* 98dB. *Output Impedance:* Less than 200 ohms.

DIGITAL SPECIFICATIONS: *Digital Input Signal Format:* Coaxial and Optical Inputs – SPDIF (PCM). *Digital Input Sample Rate:* Coaxial and Optical: 44.1kHz to 192kHz, 24-Bit. *Digital Inputs:* Coaxial: 0.5V p-p/75 ohms. Optical: -15dbm to -21dbm (TOS Link).

MB50

MEDIA BRIDGE

McIntosh
The Compendium

WI-FI CONNECTIVITY: IEEE 802.11a/b/g/n ; Wi-Fi (Dual Band). WPS.

USB CONNECTOR: Type A connector with Host Mode.

POWER CONTROL SPECIFICATIONS: **Power Control Input:** 5-15 VDC, less than 1mA. **Power Control Output:** 12 VDC, 25mA maximum total.

POWER REQUIREMENTS: 100-240 Volts, 50/60Hz at 10 Watts. Standby: Less than 0.5 watt.



MB50 - Sold from 2016 - 2023. S/N: AED1011~AED????

Size: 3-1/2"H, 11-1/2"W and 15-1/2"D behind panel. **Weight:** 8.5 pounds. **\$2,000.00**