

MS 300

DIGITAL MUSIC MANAGEMENT

McIntosh
The Compendium



FRONT PANEL: Glass with LED/fiber-optic illuminated green/gold nomenclature. Touch buttons (with indicator): GUIDE, MUSIC, RADIO. Disc drawer. IR remote sensor. Touch buttons: NAVIGate: ▲, ▼, ◀, ▶. ⚡ Touch buttons: OPEN/CLOSE, RECORD, (with indicator): ■ STOP, II PAUSE, ▶ PLAY. Digital display. Touch buttons: ◀◀ BACK, NEXT ▶▶, SELECT, FAVORites, (with indicator): STANDBY/ON.



BACK PANEL: Power cord receptacle. Inputs: IR sensor INPUT, S-LINK, DATA IN, POWER CONTROL IN. ⚡ DIGITAL AUDIO: COAX OUT, OPTICAL OUT, OPTICAL IN: 1, 2 & 3. COAX IN: 1, 2 & 3. ⚡ Left and Right AUDIO OUTPUTs. ⚡ VIDEO OUTPUTs: composite (2), s-video (2), component video output: Y, CB and CR. ⚡ Left and Right AUDIO INPUTs (3). ⚡ RS232 COMMUNICATION PORTS (4). ⚡ ETHERNET port.

AUDIO SPECIFICATIONS: *Frequency Response:* 2-20kHz \pm 1 dB. *Signal to Noise Ratio:* 102 dB (IHF A-weighted). *Dynamic Range:* >96dB. *Harmonic Distortion:* 0.01%. *Channel Separation:* 95 dB (1,000Hz). *Output Level:* 2.0 Vrms. *Output Impedance:* 200 ohm.

VIDEO SPECIFICATIONS: *Signal System:* NTSC, PAL (factory option). *Output Impedance:* 75 ohm.

GENERAL SPECIFICATIONS: *Digital Output:* optical: -15dbm to -21dbm; coaxial: 0.4Vpp to 0.6pp/75 ohm. *Digital Signal Format:* 44.1 kHz sampling frequency. *Power Requirements:* 100-240 Volts at 60 watts. Has **HR053** hand remote.

MS 300

DIGITAL MUSIC MANAGEMENT

McIntosh
The Compendium



MS 300 - Sold from 2005 - 2007. S/N: WA1001~WA???? (????? UNITS)

Size: 5-3/8"H, 17-1/2"W and 15"D. **Weight:** 20.7 lb. **\$5,100.00**