

MS 750

DIGITAL MUSIC MANAGEMENT

McIntosh
The Compendium



FRONT PANEL: Glass with LED/fiber-optic illuminated green/gold nomenclature. Touch buttons (with indicator): GUIDE, MUSIC, RADIO. Disc drawer. IR remote sensor. Touch buttons: NAVIGATE: ▲, ▼, ◀, ▶. ⚡ Touch buttons: OPEN/CLOSE, RECORD, (with indicator): ■ STOP, II PAUSE, ▶ PLAY. Digital display. Touch buttons: ⏮ BACK, NEXT ⏭, SELECT, FAVORITES, (with indicator): STANDBY/ON.



BACK PANEL: Power cord receptacle. Inputs: IR sensor input, S-LINK, DATA IN, POWER CONTROL IN. ⚡ DIGITAL AUDIO: COAX OUT, OPTICAL OUT, OPTICAL IN: 1, 2 & 3. COAX IN: 1, 2 & 3. ⚡ Left and Right ANALOG OUTPUTS. ⚡ VIDEO OUTPUTS: composite (2), S-video (2), component video output: Y, CB and CR. ⚡ Left and Right ANALOG audio inputs (3). ⚡ RS232 COMMUNICATION PORTS (4). ⚡ ETHERNET port.

AUDIO SPECIFICATIONS: **Frequency Response:** 2-22kHz $\pm$ 1 dB. **Signal to Noise Ratio:** 102 dB (IHF A-weighted). **Dynamic Range:** >96dB. **Harmonic Distortion:** 0.01%. **Channel Separation:** 95 dB (1,000Hz). **Output Level:** 2.0 Vrms. **Output Impedance:** 200 ohm.

VIDEO SPECIFICATIONS: **Signal System:** NTSC, PAL (factory option). **Output Impedance:** 75 ohm.

GENERAL SPECIFICATIONS: **Digital Output:** optical: -15dbm to -21dbm; coaxial: 0.4Vpp to 0.6pp/75 ohm. **Digital Signal Format:** 44.1 kHz sampling frequency. **Power Requirements:** 120 Volts at 60 watts. Has **HR063** hand remote.

MS 750

DIGITAL MUSIC MANAGEMENT

McIntosh
The Compendium



MS 750 - Sold from 2007 - 2010. S/N: XU1001~XU???? (????? UNITS)

Size: 6"H, 17-1/2"W and 15-7/8"D. **Weight:** 28.1 lb. **\$6,000.00**