

FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated **POWER OUTPUT** meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. switch: WATTS or HOLD. POWER switch: OFF/REMOTE or ON.



- **BACK PANEL:** POWER CONTROL jacks: IN and OUT. FUSE. Power cord receptacle. RIGHT and LEFT gold plated speaker OUTPUT terminals. MODE switch: STEREO, MONO BRIDGED or MONO PARALLEL. LEFT and RIGHT LEVEL controls: 1.4V to 2.5V. UNBALANCED RIGHT/MONO and LEFT audio INPUTS. BALANCED RIGHT/MONO and LEFT audio INPUTS.
- SPECIFICATIONS: 150w/ch. Response: 20-20kHz (+0 -0.25dB). Distortion:
 0.005%. Noise and Hum: 110dBA. Output Impedance: 2, 4 and 8 ohms.
 Damping Factor: 40 or greater. Input Impedance: 20k. Input Sensitivity:
 1.4v. Sentry Monitor. Power Guard. Autoformers. Power Requirements: 120V at 12 Amps.

CABINET: L 82







MC 150 - Sold from 1995 - 1997. S/N: LM1001~LM???? Size: 5-3/8"H, 17-1/2"W and 16-1/2"D. Weight: 59 lb. \$3,000.00

© 2007-2025 VintageMac – Larry Hodson

Rev. 09/19