

# MC 162

## STEREO POWER AMPLIFIER

# McIntosh

## The Compendium



**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. Illuminated POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ METER switch: LIGHTS OFF, WATTS or HOLD. Remote ON indicator. POWER switch: OFF, REMOTE or ON.



**BACK PANEL:** Power cord receptacle. FUSE. RIGHT and LEFT speaker output connectors. MODE switch: STEREO or BRIDGED. LEFT and RIGHT level controls: 1.4V to 2.5V. UNBALANCED Left and Right INPUTS. BALANCED Left and Right INPUTS. POWER CONTROL jacks: IN and OUT.

**SPECIFICATIONS:** 160w/ch into 4 ohms or 100w/ch into 8 ohms. (500w mono into 4 ohms or 320w mono into 8 ohms). **Response:** 20-20kHz (+0 -0.25dB). **Distortion:** 0.005%. **Noise and Hum:** -110dBA. **Output Impedance:** 4 or 8 ohms. **Damping Factor:** 100 at 4 ohms or 200 at 8 ohms. **Input Impedance:** 10k unbalanced, 22k balanced. **Input Sensitivity:** .9v. Sentry Monitor. Power Guard. Direct coupled. **Power Requirements:** 120V at 5 Amps.



# MC 162

## STEREO POWER AMPLIFIER

**McIntosh**  
The Compendium



**MC 162** - Sold from 1998 - 2003. S/N: PD1001~PD????

**Size:** 5-3/8"H, 17-1/2"W and 18-1/2"D. **Weight:** 42 lb. **\$2,200.00**