



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights.

★ METER switch: LIGHTS OFF, WATTS or HOLD. Remote ON indicator. POWER switch: OFF, REMOTE or ON.



BACK PANEL: Power cord receptacle. FUSE. RIGHT and LEFT speaker output connectors. MODE switch: STEREO OF BRIDGED. LEFT and RIGHT level controls: 1.4V to 2.5V. UNBALANCED Left and Right INPUTS. BALANCED Left and Right INPUTS. POWER CONTROL jacks: IN and OUT.

SPECIFICATIONS: 160w/ch into 4 ohms or 100w/ch into 8 ohms. (500w mono into 4 ohms or 320w mono into 8 ohms). Response: 20-20kHz (+0 -0.25dB). Distortion: 0.005%. Noise and Hum: -110dBA. Output Impedance: 4 or 8 ohms. Damping Factor: 100 at 4 ohms or 200 at 8 ohms. Input Impedance: 10k unbalanced, 22k balanced. Input Sensitivity: .9v. Sentry Monitor. Power Guard. Direct coupled. Power Requirements: 120V at 5 Amps.













MC 162 - Sold from 1998 - 2003. S/N: PD1001~PD????

Size: 5-3/8"H, 17-1/2"W and 18-1/2"D. **Weight:** 42 lb. **\$2,200.00**