


FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated left and right POWER OUTPUT meters (LINEAR WATTS OF DECIBELS). Left and right POWER GUARD lights. 

★ METER switch: LIGHTS OFF, WATTS OF HOLD. Remote ON indicator. POWER switch: OFF, REMOTE OF ON.



BACK PANEL: FUSE. Power cord receptacle. UNBALANCED Left and Right/Mono INPUTS. BALANCED Right/Mono and Left INPUTS. Mode switch: STEREO or Mono BRIDGED. POWER CONTROL jacks: In and OUT.  $\checkmark$  RIGHT speaker OUTPUT connectors for 2 Ω, 4 Ω and 8 Ω. LEFT speaker OUTPUT connectors for 2 Ω, 4 Ω and 8 Ω.

SPECIFICATIONS: 200w/ch into 2, 4 or 8 ohms. Response: 20-20kHz (+0 -0.25dB). Distortion: 0.005%. Signal to Noise Ratio: -115dBA. Output Impedance: 2, 4 or 8 ohms, mono bridged: 4, 8 or 16 ohms. Damping Factor: >40. Input Sensitivity: 1.7v unbalanced, 3.4v balanced. Dynamic Headroom: 1.9 dB. Sentry Monitor. Autoformers. Power Guard. Power Requirements: 120V at 5 Amps.















MC 202 - Sold from 2000 - 2003. S/N: RY1001~RY????

**Size:** 5-3/8"H, 17-1/2"W and 17-1/2"D. **Weight:** 65 lb. **\$3,300.00**