



FRONT PANEL: Gold and black anodized aluminum panel. Illuminated left and right POWER LEVEL meters (meters read +3 at 300w). Power indicator light. ★ LEFT GAIN control. RIGHT/MONO GAIN control. METER RANGE switch: - 20, - 10, 0, and OFF. POWER switch: ON or OFF (red on 1Yxxx through 2Yxxx units - white on most 3Yxxx and all 4Yxxx and 5Yxxx units). Handles.



- BACK PANEL: Dual cooling fans (no thermostats on 1Yxxx units. Thermostatically controlled fans on 2Yxxx through 5Yxxx units). *P* Power cord receptacle. CIRCUIT BREAKER. LEFT CHANNEL and RIGHT CHANNEL speaker OUTPUT barrier strips. Audio INPUTS: LEFT and RIGHT/MONO. MODE SWITCH: MONO or STEREO.
- SPECIFICATIONS: 300w/ch. (600w mono). Response: 20-20kHz (+0 -0.5dB). Distortion: 0.25%. Noise and Hum: -90dB. Output Impedance: 0.5, 1, 2, 4, 8 and 16 ohms. (0.25, 0.5, 1, 2, 4 and 8 ohms in mono). Damping Factor: 14 or greater. Input Impedance: 200k. Input Sensitivity: 0.5v. Sentry Monitor. Autoformer.

MC 2300 Stereo Power Amplifier

MtIntosh The Compendium



MC 2300 - Sold from 1971 - 1980. S/N: 1Y001~5Y553 (4,545 UNITS) Size: 19" rack mounting. 10-1/2"H and 17"D. Weight: 128 lb. \$1,799.00

© 2007-2025 VintageMac – Larry Hodson