

OUTPUT MODULE FRONT PANEL: LED/fiber-optic illuminated green/gold nomenclature.

Illuminated POWER OUTPUT meter (linear WATTS or DECIBELS). POWER GUARD LED.

METER mode switch: LIGHTS OFF, WATTS or HOLD. POWER switch: OFF, REMOTE or ON. Handles.



OUTPUT MODULE BACK PANEL: Speaker outputs connectors: 2Ω - A, B and C.

Speaker outputs connectors: 4Ω - A, B and C.

A, B and C.

MAIN FUSE.

Power cord receptacle. To POWER MODULE (A) 16 pin connector 1 and 2. POWER CONTROL jacks: IN and OUT. BALANCED audio OUTPUT. 2

BALANCED audio INPUTS. INPUT MODE switch: BALanced or UNBALANCED INPUT and OUTput. To POWER MODULE (B) 16 pin connector 1 and 2. Polished stainless steel chassis.



POWER MODULES (2) FRONT PANEL: LED/fiber-optic illuminated green/blue/white **McIntosh** logo and nomenclature. Handles.



POWER MODULEs (2) BACK PANEL: Polished stainless steel chassis. Power cord receptacle. **CIRCUIT BREAKER. TO OUTPUT MODULE (1)** 16 pin connector. **TO OUTPUT MODULE (2)** 16 pin connector.

SPECIFICATIONS: 2000w into 2, 4 or 8 ohms. **Response:** 20-20kHz (+0 -0.25dB). **Response:** 10-100kHz (+0 -3 dB). **Distortion:** 0.005%. **Noise and Hum:** -123dBA unbalanced, -127dBA balanced. **Output Impedance:** 2, 4 or 8 ohms. **Damping Factor:** >40. **Input Impedance:** 10k balanced. **Input Sensitivity:** 2.5v unbalanced, and 5v balanced. **Dynamic Headroom:** 2 dB. **Sentry Monitor**. **Autoformers. Quad Balanced™. Power Guard. Power Requirements:** 120V at 12 Amps.









MC 2KW - Sold from October 2005 - Current. S/N: XJ-C001~ XJ-C???

Output Module Size: 12-5/16"H, 17-3/4"W and 26-5/8"D. Weight: 121 lb.

Power Module (2 each) Size: 12-5/16"H, 17-3/4"W and 26-5/8"D. Weight: 158 lb.

\$30,000.00