

FRONT PANEL: Glass with LED/fiber-optic illuminated green nomenclature. Illuminated **POWER OUTPUT** meter (linear **WATTS** or **DECIBELS**). **POWER GUARD** light. **4** Standby Power On Indicator. **4 METER LIGHT** switch: **ON** or **OFF**. **POWER** switch: **ON** or **OFF**.



BACK PANEL: INPUT MODE switch: BALanced or UNBALanced. BALanced INput. UNBALanced In/Out, BALanced OUTput. POWER CONTROL jacks: IN and OUT. AUTO OFF Power Save switch: DISabled or ENAbled. ✓ FUSE. Power cord receptacle. Gold plated speaker OUTPUT terminals for 2, 4 and 8 ohms.

SPECIFICATIONS: 300w. Frequency Response: 20-20kHz (+0 -0.25dB), 10- 100kHz (+0 -3.0dB). Distortion: 0.005%. Signal to Noise Ratio: -95dBA, balanced; -93dBA, unbalanced. Dynamic Headroom: 2dB. Output Impedance: 2, 4 or 8 ohms. Damping Factor: 40 or greater. Input Impedance: 22k, balanced or unbalanced. Input Sensitivity: 3.4v, balanced; 1.7, unbalanced. Voltage Gain: 23dB, 2 ohms; 26dB, 4 ohms; 29dB, 8 ohms. Sentry Monitor. Power Guard. Quad Balanced™. Autoformer. Power Requirements: 120V at 3.7 Amps.





MC 301 - Sold from 2014 - 2021. S/N: ADU1001~ADU???? Size: 6"H, 17-1/2"W and 21"D. Weight: 67 lb. \$5,000.00

© 2007-2025 VintageMac – Larry Hodson