



FRONT PANEL: Glass with LED/fiber-optic illuminated green/gold nomenclature. Channel 1, 2 and 3 POWER GUARD indicators.
 ✓ Illuminated channel 1, 2 and 3 POWER OUTPUT meters (linear WATTS or DECIBELS).
 ✓ METER LIGHTS switch: OFF, AUTO. Standby power on indicator. POWER switch: OFF, REMOTE or ON. Handles.



BACK PANEL: Polished stainless steel chassis. [BALanced audio INPUT 3. ↓ UNBALanced audio INPUT 3. ↓ POWER CONTROL jacks: IN and OUT.] ↓ [BALanced audio INPUT 2. ↓ UNBALanced audio INPUT 2. ↓ BALanced audio INPUT 1. UNBALanced audio INPUT 1.] ↓ OUTPUT 3 binding posts for 2 Ω, 4 Ω or 8 Ω speakers. Power cord receptacle. OUTPUT 2 binding posts for 2 Ω, 4 Ω or 8 Ω speakers. FUSE. OUTPUT 1 binding posts for 2 Ω, 4 Ω or 8 Ω speakers.

SPECIFICATIONS: 300w/ch into 2, 4 or 8 ohms. Response: 20-20kHz (+0 -0.25dB).
 Distortion: 0.005%. Signal to Noise Ratio: -112dBA. Output Impedance: 2, 4, or 8 ohms. Damping Factor: greater than 40. Input impedance: 10K. Input Sensitivity: 3.4v balanced and 1.7v unbalanced. Dynamic Headroom: 1.8 dB. Sentry Monitor. Power Guard. Autoformers. Power requirements 120V at 10 Amps.





 MC 303 - Sold from 2008 - Current.
 S/N: ZH1001~ZH???? and ADC1??1~ ADC????

 Size: 12-3/8"H, 17-3/4"W and 22"D.
 Weight: 155 lbs.

 \$10,000.00

© 2007-2025 VintageMac – Larry Hodson