

FRONT PANEL: Glass with LED/fiber-optic illuminated green/gold nomenclature.

Illuminated left and right POWER OUTPUT meters (linear WATTS or DECIBELS). Left and right POWER GUARD lights. Remote ON indicator light.

★ METER switch: LIGHTS OFF, WATTS OF HOLD. POWER switch: OFF, REMOTE OF ON.



BACK PANEL: POWER CONTROL jacks: OUT and IN. BALANCED Right/MONO and Left INPUTS. UNBALANCED Left and Right/MONO INPUTS. INPUT MODE: UNBALANCED or BALANCED. \checkmark Polished stainless steel chassis. Power cord receptacle. FUSE. RIGHT channel OUTPUT binding posts for 2 Ω , 4 Ω or 8 Ω speakers. LEFT channel OUTPUT binding posts for 2 Ω , 4 Ω or 8 Ω speakers.

SPECIFICATIONS: 400w/ch. (800w mono). Response: 20-20kHz (+0-0.25dB).

Distortion: 0.005%. Signal to Noise Ratio: -124dBA balanced, -120dBA unbalanced. Output Impedance: 2, 4, or 8 ohms stereo, 1, 2 or 4 ohms mono.

Damping Factor: >40. Input Impedance: 10K balanced and 20K unbalanced.

Input Sensitivity: 4v balanced and 2.0v unbalanced. Dynamic Headroom: 2.1 dB. Sentry Monitor. Autoformers. Quad Balanced™. Power Guard. Power requirements 120V at 10 Amps.









MC 402 - Sold from 2002 - 2014. S/N: UH1001~UH???? (PRE-ROHAS) & XC1001~XC???? (POST-ROHAS [DEC. 2006])

Size: 9-7/16"H, 17-1/2"W and 20"D. **Weight:** 110-1/2 lb. **\$5,100.00**