

MC 500

STEREO POWER AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated LEFT and RIGHT POWER OUTPUT meters (linear WATTS or DECIBELS). ⚡ Left and right POWER GUARD lights. ⚡ METER switch: WATTS or HOLD. POWER switch: OFF/REMOTE or ON. Handles.



BACK PANEL: Power cord receptacle. CIRCUIT BREAKER. POWER CONTROL jacks: IN and OUT. LEFT and RIGHT gold plated speaker OUTPUT terminals. LEFT and RIGHT BALANCED audio INPUT. LEFT and RIGHT UNBALANCED audio INPUT. MODE switch: STEREO or BRIDGED. Early units had black-painted chassis - later units had stainless steel chassis.


MC 500

STEREO POWER AMPLIFIER

McIntosh

The Compendium

SPECIFICATIONS: 500w/ch. (1000w mono). **Response:** 20-20kHz (+0 -0.25dB).
Distortion: 0.005%. **Noise and Hum:** -115dBA. **Output Impedance:** 2, 4 and 8 ohms. (4, 8 and 16 ohms in mono). **Damping Factor:** 200 or greater. **Input Impedance:** 10k. **Input Sensitivity:** 2.2v. Sentry Monitor. Power Guard. Autoformers.



MC 500 - Sold from 1994 - 1999. S/N: KE1001~KE????

Size: 10-3/8"H, 17-1/4"W and 20-1/8"D. **Weight:** 114 lb. **\$7,000.00**