



FRONT PANEL: Glass with LED/fiber-optic illuminated green/gold nomenclature. Illuminated **POWER OUTPUT** meter (linear **WATTS** or **DECIBELS**). **POWER GUARD** light. **† METER** switch: LIGHTS OFF, WATTS or **HOLD**. Remote ON indicator light. **POWER** switch: OFF, REMOTE or ON. Handles.



BACK PANEL: Polished stainless steel chassis. Power cord receptacle. FUSE. OUTPUT binding posts for 2 Ω , 4 Ω or 8 Ω speakers. POWER CONTROL jacks: OUT and IN. BALANCED audio INPUT. INPUT MODE switch: BALANCED or UNBALANCED. UNBALANCED audio INPUT.

SPECIFICATIONS: 500w into 2, 4 or 8 ohms. Response: 20-20kHz (+0 -0.25dB).
Distortion: 0.005%. Signal to Noise Ratio: -124dBA balanced and unbalanced.
Output Impedance: 2, 4, or 8 ohms. Damping Factor: 100 at 8 ohms. Input Impedance: 20K ohms balanced and 10K ohms unbalanced. Input Sensitivity: 4.2v balanced and 2.1v unbalanced. Dynamic Headroom: 1.8 dB. Sentry Monitor.
Autoformer. Quad Balanced™. Power Guard. Power requirements 120V at 6.6 Amps.





MC 501 - Sold from 2003 - 2013. S/N: UM1001~UM???? (PRE-ROHAS) and WU1001~WU???? (POST-ROHAS).

Size: 8-13/16"H, 17-1/2"W and 14-13/16"D. *Weight:* 105-1/2 lbs. *\$4,100.00*

© 2007-2025 VintageMac – Larry Hodson