MONAURAL POWER AMPLIFIER





FRONT PANEL: Glass with LED green nomenclature. Illuminated POWER OUTPUT meter (linear watts or decibels). Power quard LED. Standby power On indicator. 🗲 METER switch: LIGHTS OFF, WATTS or HOLD. POWER switch: OFF, REMOTE or ON. Handles.



BACK PANEL: POWER CONTROL jacks: IN, OUT 1 and 2. BALanced INput. INput/OUTput. BALanced OUTput. INPUT MODE switch: UNBALanced or BALanced. Polished stainless steel chassis. Gold plated output terminals for 8 Ω , 4 Ω , or 2 Ω speakers. **FUSE**. Power cord receptacle.

SPECIFICATIONS: 600w into 2, 4 or 8 ohms. **Response:** 20-20kHz. Distortion: 0.005%. Signal to Noise Ratio: -96dBA balanced, -94dBA unbalanced. Output Impedance: 2, 4, or 8 ohms. Wide Band Damping Factor: greater than 40. Input Impedance: 22K balanced and unbalanced. Input Sensitivity: balanced and 2.4v unbalanced. **Dynamic Headroom:** 1.8 dB. Sentry Monitor. Power Guard. Autoformers, Quad Balanced™. Power requirements 120V at 6.6 Amps.





MC 601 - Sold from 2011 - 2020. S/N: ACH1001~ACH???? and AAY1001~AAY????

Size: 9-7/16"H, 29-1/2"W and 22"D. **Weight:** 93 lbs. **\$6,000.00**