MONAURAL POWER AMPLIFIER



The Compendium



FRONT PANEL: Glass with LED green nomenclature. Illuminated POWER OUTPUT meter (linear WATTS or DECIBELS). Power guard LED. Standby power On indicator. ← METER switch: LIGHTS OFF, WATTS or HOLD. POWER switch: OFF, REMOTE or ON. Handles.



BACK PANEL: POWER CONTROL jacks: IN, OUT 1 and 2. BALanced OUTput. UNBALanced: INput/OUTput. BALanced INput. AUTO OFF: ENabled or DISabled. INPUT MODE switch: UNBALanced or BALanced. \checkmark Polished stainless steel chassis. FUSE. Gold plated OUTPUT terminals for 8 Ω , 4 Ω , or 2 Ω speakers. \checkmark Power cord receptacle.

SPECIFICATIONS: 600w into 2, 4 or 8 ohms. **Response:** 20-20kHz +0,-0.25dB; 20-100kHz +0,-3.0dB **Distortion:** 0.005%. **Signal to Noise Ratio:** -124dBA balanced, -120dBA unbalanced. **Output Impedance:** 2, 4, or 8 ohms. **Wide Band Damping Factor:** greater than 40. **Input Impedance:** 22K balanced and unbalanced. **Input Sensitivity:** 4.8v balanced and 2.4v unbalanced. **Dynamic Headroom:** 2.8 dB. **Sentry Monitor. Power Guard. Autoformers. Quad Balanced™.** Power requirements 120V at 6.6 Amps.





MC 611 - Sold from February 2018 - Current. S/N: AGF1001~AGF????

Size: 9-7/16"H, 29-1/2"W and 22"D. Weight: 97.5 lbs. \$7,500.00