MC 75 60th Anniversary

MONAURAL POWER AMPLIFIER





CONTROLS & CONNECTORS: Titanium gold plated stainless steel/black chassis. OUTPUT connectors for common, 2, 4 and 8 OHMS. POWER CONTROL jacks: IN / OUT. INPUT SENSITIVITY switch: 1.7V or .85V. BALANCED audio XLR INPUT jack, IN/OUTPUt jack. INPUT switch: BALanced or UNBALanced. UNBALANCED audio INPUT / IN/OUTPUt jack. POWER switch OFF/ STandby or ON. Standby/Power On and Sentry Monitor tube protection activation indicator.





REAR: Power cord socket. \checkmark Fuse holder.

SPECIFICATIONS: 75w into 2, 4 or 8 ohms. Response: 20-20kHz (+0, -.5dB).

Distortion: .5% maximum harmonic distortion at any power level from 250 milliwatts to rated power, 20Hz to 20,000Hz. **Noise & Hum:** -110dB below rated output. **Output Load Impedance:** 2, 4, 8 ohms. **Wide Band Damping Factor:** Greater than 18. **Input Impedance:** 20,000 ohms Unbalanced 15,000 ohms Balanced. **Input Sensitivity:** (for rated output) 1.7 Volt or 0.85 Volt Unbalanced; 3.4 Volt or 1.7 Volt Balanced. **Unity Coupled. Power Requirements:** 120V at 1.8 Amps.

TUBES: 2-KT88 output, 1 - 12AX7A, 2 - 12AT7. Solid state rectifier.

MC 75 60th Anniversary







Originally sold as part of the McIntosh 60^{th} Anniversary combination of C22 pre-amp and pair of MC 75 power amplifiers.



MC 75 60th Anniversary - Sold from 2009 - 2010. S/N: RAV-???- RAV-??? (?,??? UNITS) Size: 8-1/2"H, 8-1/2"W and 17-3/4"D. Weight: 38 lb.

60th Anniversary combination **C22/MC75** (2) **\$15,000.00**