


FRONT PANEL: Brushed aluminum and glass with LED/fiber-optic illuminated green nomenclature. **OUTLET CONTROL / SETUP** menu knob. **SWITCHED OUTLETS** indicators. Digital display. AC power indicator. **DISPLAY CONTROL / ADJUST** menu knob.





BACK PANEL: SWITCHED OUTLET 3, SWITCHED OUTLET 2, SWITCHED OUTLET 1, UNSWITCHED OUTLET. Circuit breaker. Power cord receptacle. CONTROL 2: IN and OUT; POWER CONTROL 1: IN and OUT. MAIN POWER CONTROL: IN and OUT. RS232 CONTROL.



[220-240V Version with Type F (a.k.a. CEE 7/3 or "Schuko") receptacles]

VOLTAGE AND POWER SPECIFICATIONS MIP 200 (100V-120V): Input Rating:

100V 50/60Hz 12A (Max); 110V 50/60Hz 12A (Max); 120V 50/60HZ 12A (Max). **Output Rating:** 11.6A (1160W) Total. **AC Surge Protection:** Thermally Protected Metal Oxide Varistor (TPMOV) 50 kA – 8/20μs Line to Neutral. **AC Voltage Protection:** ±5% or ±10% from Nominal. **Power Control Output:** 12VDC, 25mA (Main); Vout = Vin (PC1, PC2, PC3).

VOLTAGE AND POWER SPECIFICATIONS MIP 200 (220V-240V): Input Rating:

220V 50/60Hz 6A (Max); 230V 50/60Hz 6A (Max); 240V 50/60HZ 6A (Max). *Output Rating:* 5.8A (1275W) Total. *AC Surge Protection:* Thermally Protected Metal Oxide Varistor (TPMOV) 50 kA – 8/20µs Line to Neutral. *AC Voltage Protection:* ±5% or ±10% from Nominal. *Power Control Output:* 12VDC, 25mA (Main); Vout = Vin (PC1, PC2, PC3).



MIP 200 - Sold from September 2024 - Current. S/N: ???1001~??????? (?,???? UNITS) 110V Version Size: 4-3/8"H, 17-1/2"W and 15-9/16"D behind panel. 220V Version Size: 4-3/8"H, 17-1/2"W and 15-23/32"D behind panel.

Weight: 17 lb. **\$3,000.00**