The Compendium





[110-120V Version with Type B (a.k.a. NEMA 5-15R) receptacles]

BACK PANEL: POWER CONTROL: LOCAL OUT and IN: 4, 3, 2; GLOBAL OUT and IN: 1. PROTECTED: NET IN and OUT; ANTENNA IN and OUT; RS232 OUT and IN. OUTLETS: 4, 3, 2. UNSWITCHED OUTLETS: 1. Circuit breaker. Power cord receptacle.

MPC 500 PROTECTION AND TECHNOLOGIES: AC Mains Protection: Surge: 20kA (8x20kA) PER MODE. Modes of Protection: RS232 Connections: Thermally Protected and Low Voltage DC Protection: Surge: 5kA (8x20us); Maximum Operating Voltage: 15VDC; Maximum Operating Current: 350mA; DC Clamping Voltage: 24Volts; Technology: GDT, PTC and TVS. ETHERNET Connections: Thermally Protected and Low Voltage DC Protection: Surge: 10kA (8x20us); Maximum Operating Voltage: 58VDC; Technology: TVS. COAXIAL Connections: Thermally protected and Low Voltage DC Protection: Surge: 5kA (8x20us); DC Clamping Voltage: 75VDC; Technology: GDT.

VOLTAGE AND POWER SPECIFICATIONS MPC 500 (100V-120V): Input Voltages:

100 - 120 Volts AC Nominal; **Output Voltages:** 100 - 120 Volts AC Nominal; **Power Requirements:** 100V - 120V ~ 50/60Hz; 12.0 Amps, maximum current; 1440 Watts, maximum wattage.



[220-240V Version with Type F (a.k.a. CEE 7/3 or "Schuko") receptacles]

BACK PANEL: POWER CONTROL: LOCAL OUT and IN: 4, 3, 2; GLOBAL OUT and IN: 1. PROTECTED: NET IN and OUT; ANTENNA IN and OUT; RS232 OUT and IN. OUTLETS: 4, 3, 2. UNSWITCHED OUTLETS: 1. Circuit breaker. Power cord receptacle.

VOLTAGE AND POWER SPECIFICATIONS MPC 500 (220V-240V): Input Voltages: 220 - 240 Volts AC Nominal; Output Voltages: 220 - 240 Volts AC Nominal; Power Requirements: 220V - 240V ~ 50/60Hz; 6.0 Amps, maximum current; 1440 Watts, maximum wattage.



MPC 500 - Sold from 2019 - Current. **S/N: AHA1001~AHA????** (?,???? UNITS) *Size:* 6"H, 17-1/2"W and 19"D behind panel. *Weight:* 18.5 lb. *\$2,500.00*

© 2007-2025 VintageMac – Larry Hodson