

C 200C – CONTROLLER FRONT PANEL: Glass with illuminated teal/gold nomenclature. BALANCE: L to R. RECORD. Digital display. LISTEN. VOLUME. ☆ IR sensor. Touch buttons (with indicator lights): RECORD PROCESSOR, LISTEN PROCESSOR, RECORD MONITOR, MONO, SETUP, DISPLAY: dB or %, MUTE, OUTPUTS 1, OUTPUTS 2, STANDBY/ON. POWER: ON OR OFF.



C 200C – CONTROLLER BACK PANEL: 25 pin TO C 200 PREAMPLIFIER connector. POWER CONTROL: MAIN, ACC, 1 and 2. DATA PORTS: TP 1, TUNER, PH/AUX 1, PH/AUX 2, CD, TAPE 2, TAPE 1, LINE 1. PASS THRU power control. Coax EXTERNAL SENSOR connector. Power cord receptacle. FUSE.

SPECIFICATIONS: Response: 10-40kHz (+0 -0.5dB). Distortion: 0.002%. Noise and Hum: – 100dB high level, -86dB phono. Maximum Output: 12V unbalanced, 25V balanced. Output Impedance: 50 ohms. Input Sensitivity and Impedance: high level 0.45V (5V max) at 22k unbalanced and 44k balanced, phono MM 4.4mV (50mV max) at 47k and 65pF. Power Requirements: 120V at 30 Watts. Has HR100 remote control.

Size: 6"H, 17-1/2"W and 20"D behind panel. Weight: 26 lb. S/N: SX1001~SY????



C 200P - *PREAMPLIFIER FRONT PANEL:* LED/fiber-optic illuminated green/gold nomenclature. Power on light. **HEADPHONES** jack.





C 200 -Sold from 2000 - 2008. S/N: SY1001~SY????

Size: 6"H, 17-1/2"W and 20"D behind panel. Weight: 20.5 lb. Both preamp and power controller \$7,000.00