



FRONT PANEL: Glass with LED/fiber-optic illuminated green/gold nomenclature. BASS. TREBLE. Digital display. INPUT. VOLUME. ★ HEADPHONES jack. IR sensor. Touch buttons: TONE BYPASS / MENU, 6 CHannel MODE / ENTER (with indicator), TRIM LEVEL / TUNE: ▼ or ▲, TRIM, SETUP, MUTE, STANDBY/ON (with indicator), POWER: ON or OFF.



SPECIFICATIONS: Response: 20-20kHz (+0 -0.5dB). Distortion: 0.002%. Noise and Hum: – 96dB aux, -86dB phono. Output Rated: 2.5V unbalanced and 5.0V balanced. Maximum Output: 8V unbalanced and 16V balanced. Input Sensitivity and Impedance: high level 0.45V (5V max) at 22k unbalanced and 0.90V (10V max) at 50k balanced, phono 4.5mV (50mV max) at 47k and 65pF. Tone Controls: bass and treble boost and cut 12dB. Voltage Gain: 15dB high level, 55dB phono. Power Requirements: 120V at 35 Watts. Has hand remote HR044 remote and HR093 replacement.

C 45 6-CHANNEL PRE-AMPLIFIER / VIDEO CONTROL CENTER











C 45 - Sold from 2003 - 2010. S/N: XF1001~XF???? and VD1001~VD???? Size: 6"H, 17-1/2"W and 16-1/2"D behind panel. Weight: 21 lb. \$3,600.00

© 2007-2025 VintageMac – Larry Hodson