



FRONT PANEL: Glass with illuminated teal/gold nomenclature. INPUT SELECTOR: AUX,
TUNER, PHONO 1, and PHONO 2. Pushbutton switches: POWER: ON OF OFF, TAPE 1 MONITOR:
IN OF OUT, TAPE 2 MONITOR: IN OF OUT, TAPE COPY: 1→2 OF 2→1, MONO: IN OF OUT.
HEADPHONES jack. EQUALIZER FREQUENCY controls: 30, 750 and 10k. Concentric
BALANCE: L to R / LOUD: FLAT to MAX. VOLUME. PANLOC buttons.



BACK PANEL: AC outlets: 4 SWITCHED, 2 UNSWITCHED. OUTPUTS: TAPE 2, TAPE 1, MAIN.

INPUTS: TAPE 2, TAPE 1, TUNER.

PH 2, PH 1, AUX. Ground binding post. Panloc mounting.

SPECIFICATIONS: Response: 20-20kHz (+0-0.5dB). Distortion: 0.02%. Noise and Hum: - 80dB aux, -90dB phono. Output Rated: 2.5v, 10v max. Output Impedance: 100 ohms. Load Impedance: 5k. Input Sensitivity and Impedance: aux 0.25V at 47k, phono 2.2mV at 47k and 50pF. Equalizer Controls: boost and cut 12dB. Loudness continuously variable. Voltage Gain: 20dB aux, 61.1dB phono. Power Requirements: 120V at 25 Watts.

CABINET: L 50



C 504 STEREO PRE-AMPLIFIER

MtIntosh The Compendium















C 504 - Sold from April 1980 - October 1988. S/N: CN1001~CN3550 (2,549 UNITS)

Size: 3-5/8"H, 16"W and 14-1/2"D behind panel. Weight: 14 lb. \$1,090.00