STEREO PRE-AMPLIFIER / VIDEO CONTROL CENTER





FRONT PANEL: Glass with illuminated teal/gold nomenclature. INPUT selector: CD1, CD2, TUNER, VIDEO, PH/AUX. BASS. TREBLE. BALANCE: L to R. LOUDNESS: FLAT tO MAX. VOLUME.

Touch buttons (with indicators): MONO, TAPE MON 1, TAPE MON 2. HEADPHONES jack. TAPE COPY 1▶2, TAPE COPY 2▶1, POWER: ON or OFF.



BACK PANEL: SWITCHED AC outlet. Right and Left BALANCED OUTPUTS. OUTPUTS: MAIN, TAPE 2, TAPE 1. PROCESSOR: FROM and TO. INPUTS: TAPE 2, TAPE 1, VIDEO, TUNER, CD2, CD1, AUX, PH.

→ Power cord. Power Control jack. DATA ports: SUM, TAPE 2, TAPE 1, VIDEO, TUNER, CD 2, CD 1, AUX. Ground binding post.

SPECIFICATIONS: Response: 20-20kHz (+0-0.5dB). Distortion: 0.002%. Noise and Hum: - 105dB aux, -90dB phono. Output Rated: 2.5v, 8V max. Input Sensitivity and Impedance: high level 0.25V (10V max) at 22k, phono 2.5mV (90mV max) at 47k and 65pF. Tone Controls: bass and treble boost and cut 12dB. Loudness continuously variable. Voltage Gain: 20dB aux, 60dB phono. Power Requirements: 120V at ?? Watts.

Same as the **C 712**, but without remote control capability.

CABINET: L 70

C 710 STEREO PRE-AMPLIFIER /

VIDEO CONTROL CENTER











C 710 - Sold from 1993 - 1995. S/N: JN1001~JN????

Size: 3-5/8"H, 17-1/2"W and 17-1/2"D behind panel. Weight: 17 lb. \$???.00