

D 1100

DIGITAL PRE-AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Glass with LED/fiber-optic illuminated green nomenclature. Illuminated left relative OUTPUT LEVEL meter (DECIBELS). Digital information display. Illuminated right relative OUTPUT LEVEL meter (DECIBELS). ⚡ INPUT / TRIM / SETUP SELECTOR. IR sensor. 1/4" HEADPHONES jack. Touch buttons (with indicator lights): OUTPUTS 1 AND 2. Touch button: MUTE. Touch button (with indicator light): STANDBY/ON / RESET. VOLUME / TRIM / SETUP control.



BACK PANEL: RIGHT OUTPUT 2: UNBALANCED and BALANCED. RIGHT OUTPUT 1: UNBALANCED and BALANCED. RIGHT FIXED OUTPUT: UNBALANCED and BALANCED. LEFT FIXED OUTPUT: BALANCED and UNBALANCED. LEFT OUTPUT 1: BALANCED and UNBALANCED. LEFT OUTPUT 2: BALANCED and UNBALANCED. ⚡ Power cord receptacle. DIGITAL AUDIO INPUTS: AES/EBU XLR, COAXIAL: 1, 2, 3; OPTICAL: 1, 2, 3; MCT; USB (UPDATE). POWER CONTROL: TRIGGER 1 / TRIGGER 2, TRIGGER 3 / TRIGGER 4. DATA PORTS: 1 / 2, 3 / 4. EXTERNAL CONTROL: Infra-Red input / RS232 connector; ANALOG PREAMP.

D 1100

DIGITAL PRE-AMPLIFIER

McIntosh

The Compendium

AUDIO SPECIFICATIONS: *Frequency Response:* +0, -0.5dB from 20Hz to 20,000Hz; +0, -3dB from 4Hz to 68,000Hz. *Total Harmonic Distortion:* 0.0015% (at 2V Output). *Fixed Output Level:* 2.0Vrms Unbalanced; 4.0Vrms Balanced. *Variable Output Level:* 0 – 9.0Vrms Unbalanced; 4.0Vrms Balanced. *Maximum Output:* 8V RMS Unbalanced, 16V RMS Balanced, 0 – 16.0Vrms Balanced. *Signal To Noise Ratio (A-Weighted):* 111dB. *Dynamic Range:* 100dB. *Output Impedance:* 100 ohms Unbalanced and Balanced. *Headphone Load Impedance:* 20 to 600 ohms.

DIGITAL AUDIO SPECIFICATIONS: *Digital Input Signal Format:* Coaxial, Optical and AES/EBU Inputs – SPDIF (PCM); MCT and USB Inputs – PCM, DSD. *Digital Input Sample Rates:* Coaxial, Optical and AES/EBU: 44.1kHz to 192kHz, 24-Bit; MCT: 44.1kHz, 16-Bit (CD), DSD64 (SACD); USB: 44.1kHz to 385kHz, 32-Bit (PCM); DSD64, DSD,128, DSD256, DXD352.8kHz, DXD384kHz. *Digital Inputs:* Coaxial: 0.5V p-p/75 ohms; Optical: -15dbm to -21dbm (TOS Link); MT: 0.5V p-p/75 ohms; USB: USB Type B Connector.

GENERAL SPECIFICATIONS: *Power Control:* 12VDC, 25mA. *Power Requirements:* 120 Volts, 50/60Hz at 30 watts. Has hand remote **HR085**.



D 1100 -Sold from 2016 - 2024. S/N: AFG1001~AFG????

Size: 6"H, 17-1/2"W and 19"D behind panel. **Weight:** 26 lb. **\$7,000.00**