

SL 1

POWERED SUBWOOFER

McIntosh
The Compendium



FRONT PANEL: Power switch with indicator lights: off or on/standby. High pass frequency control: 50 to 125Hz with labels at 50, 63, 80, 100 and 125Hz. Subwoofer frequency control: 50 to 125Hz with labels at 50, 63, 80, 100 and 125Hz. Level control: 0 to max. Control mode switch: variable or THX. Phase switch: 0 or 180.

BACK PANEL: High input barrier strip. R/Mono input connector. Line input. Hi pass output. THX/mono. Power control connectors: in and out. Fuse.

AMPLIFIER: 250w into 4 ohms. **Distortion:** .005%. **Hum and Noise:** -115dBA. **IHF Dynamic Headroom:** 1.1dB. **Input Sensitivity:** THX 0.1V, variable mode 0.4V (9.0V max). **Input Impedance:** 15k. Power Guard.

LOUDSPEAKER: one 12" LD/HP Front facing woofer. **Frequency Response:** 20-350Hz (THX mode).

OTHER: Black ash or walnut veneer. Magnetic-shielding. THX approved.

SL 1 - Sold from 1997 - 2001. S/N: NJ1001~NJ???? (? ,???? UNITS)

Size: 18-3/4"H, 16-1/2"W and 19"D. **Weight:** 85 lb. **\$2,000.00**